



MODULAR SPECIFICATIONS




Style Number..... GT086
 Style Name Connexion Modular
 Construction tufted
 Surface Texture..... textured patterned cut and loop
 Gauge 1/12 (47.00 rows per 10 cm)
 Density..... 9,853
 Weight Density 256,178
 Stitches Per Inch..... 14.2 (55.91 per 10 cm)
 Protective Treatment... DuraTech
 Finished Pile Thickness .095" (2.41 mm)
 Dye Method..... solution dyed/yard dyed
 Backing Material..... EcoFlex ICT
 Fiber Type Duracolor® Premium Nylon with Antron® Legacy
 Fiber Technology Duracolor® by LEES Stain Resistant System.
 Passes GSA requirements for permanent stain resistant carpet.
 Face Weight..... 26 oz/yd2 (881.66 gm/m2)
 Size/Width 24" x 24" (60.9 cm x 60.9 cm)
 Installation Method.... monolithic
 IAQ Green Label Plus.. 1098
 CRI Rating..... Severe Traffic
 Pattern Repeat Not Applicable
 Warranties Lifetime Limited Modular Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static



104
BIRCH



108
SEASPRAY



124
BAMBOO SPROUT



201
BEACH GLASS




204
RIVERBEND



208
HEMATITE



301
NATURE'S ESSENCE



308
BRONZE SCULPTURE



348
NAUTICA



403
BONFIRE



408
STORM



508
NORDIC SHADOW