



MODULAR SPECIFICATIONS



Style Number LT110
 For Borders Only
 Style Name Coordination EcoFlex AIR Modular
 Construction tufted
 Surface Texture..... level solid cut and loop
 Gauge 1/10" (39.37/10 cm)
 Density..... 8,667
 Weight Density..... 225,342
 Stitches Per Inch..... 11.0 per inch (43.30/10 cm)
 Protective Treatment... Sentry Plus
 Finished Pile Thickness....108" (2.74 mm)
 Dye Method..... solution dyed
 Backing Material..... EcoFlex AIR
 Fiber Type Colorstrand SD Nylon
 Face Weight..... 26 oz/yd2 (881.66 gm/m2)
 Size/Width 24" x 24" (60.9 cm x 60.9 cm)
 Installation Method..... quarter turn/borders only
 IAQ Green Label Plus.. 2771
 CRI Rating..... Heavy Traffic
 Pattern Repeat Not Applicable
 Warranties Lifetime Limited Modular Warranty, Lifetime
 Limited Colorfastness to Light, 10 year
 Limited Colorfastness to Atmospheric
 Contaminants, 10 Year Stain Warranty



8545 Actual



8383 Applicable



8718 Arrange



8646 Border



8738 Combine



8658 Common



8238 Complete



8828 Concur



8936 Connect



8585 Correlate



8899 Definite



8556 Equate



8878 Exact



8868 Fasten




8821 Fit



8628 Fusing



8656 Goes With



8985 Harmonize



8611 In Cahoots



8566 Inset



8252 Linking



8822 Match Up



8989 Mingle



8898 Mix



8696 Organize



8262 Pair



8695 Pertinent



8978 Pool



8555 Relate



8343 Relevant



8333 Same As



8979 Share



8388 Suitable



8536 Sure Fit



8253 This One



8939 Unite



8484 Usable