



MODULAR SPECIFICATIONS

Style NumberGT096
 Style NameData Overload Modular
 Collection.....Digital Infusion
 Constructiontufted
 Surface Texturetextured patterned cut and loop
 Gauge1/12 (47.00 rows per 10 cm)
 Density5,824
 Weight Density128,128
 Stitches Per Inch11.2 per inch (44.09 per 10 cm)
 Protective Treatment ...DuraTech
 Finished Pile Thickness .136" (3.45 mm)
 Dye Methodsolution dyed/yarn dyed
 Backing MaterialEcoFlex ICT
 Face YarnDuracolor® Premium Fiber with Antron®
Legacy
 Fiber TechnologyDuracolor® by LEES Stain Resistant System.
Passes GSA requirements for permanent
stain resistant carpet.
 Face Weight22 oz/yd2 (746.02 gm/m2)
 Size/Width24" x 24" (.6096 m x .6096 m)
 Installation Method ...monolithic, vertical ashlar, brick ashlar,
quarter turn
 IAQ Green Label Plus..1098
 CRI Ratingsevere traffic
 Pattern RepeatNot Applicable
 WarrantiesLifetime Limited Modular Warranty, Lifetime
 Duracolor Stain Warranty, Lifetime Static



101
TRANSIENT
COLOR



204
VISUAL
STIMULATION



206
REFLECTIVE
SYNERGY



208
MULTIFACETED
FORMAT



226
SOLARIZED
PATH



228
REFRACTED
LIGHT



304
DAPPLED
GRADIENT



308
ALTERED
STATE



327
STATIC
ILLUSION



328
DISTORTED
IMAGE



403
MORPHED
ENERGY



404
GLITCH
ART